SAN DECO®
Paint Manufacturing & Distribution

ACRYTEX ELITE

Exterior Textured Coating

ACRYTEX ELITE is a textured surface coating developed for both indoor and outdoor applications. Thanks to its special filler content, it enables various texture applications.

WATER BASED · LOW VOC · TINTABLE

Acrytex Elite contains special fillers with a size of 2mm.

Easy to apply. Allows effortless creation of patterns and textures.

Thanks to its fiber content, it enables thick textured applications without cracking.

Its elastic structure acts as a bridge over cracks on the application surface.

Due to the 2mm film layer it forms during application, it easily covers surface defects and imperfections.

Formulated to withstand exterior weather conditions.

High water vapor permeability allows water vapor to escape and enables the surface to breathe.

Helps thermal insulation thanks to its internal filler structure.

Water-based. Safe for human health and environmentally friendly.

CONTENT: *Acrylic-based – Water-based*	PACKAGING: *25 KG*
THINNING: *Ready to use; do not dilute.*	DRYING TIME: *At 23 °C and 50% relative humidity: Touch dry in 4–6 hours; full cure in 24–48 hours.*
PRIMER: *San Deco Decoprimer*	FULLY DRY: *24–48 hours*
APPLICATION TOOL: *Trowel*	COLORING: -
NUMBER of COATS: *1*	VOC: *EU Limit Value (Directive 2004/42/EC): Category A/l: Decorative effect coatings (water-based): 200 g/l (2010). Acrytex Elite contains max. 20 g/l VOC.*
STORAGE and SHELF LIFE: *Can be stored for up to 2 years in unopened original packaging, in a cool and dry place, protected from direct sunlight, at temperatures between +5 °C and +35 °C.*	

CONSUMPTION - Single Coat : *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.*

Paint consumption per 1 m^2 area is 1.6 – 2.2 kg.

APPLICATION AREA

It is used as a coating material on interior and exterior walls, plaster, exposed concrete, and wooden surfaces following appropriate surface preparation, applied over its specified primer.

SURFACE PREPARATION

After cleaning all dirt, grease, loose paint, and dust from the application surfaces, surface irregularities should be leveled with San Deco Acrylic Putty Thick (San Deco Akrilik Macun Kalın) and primed with San Deco Decoprimer.

SURFACE CONDITION

Ensure ambient temperature is between +5 °C and +35 °C during application and for the subsequent 24 hours.

Ambient humidity during application should be below 75%.

Surface moisture content must be below 10%.

APPLICATION

Acrytex Elite is applied as a single coat. Mix thoroughly until homogenous before use without dilution.

Apply using a steel trowel.

The application thickness is adjusted according to the products's maximum grain size.

Textures and patterns can be created using a roller or trowel as desired.

It is recommended to use a single batch of product for the same project.

If multiple batches are used, mix equal proportions of batches together to avoid color and texture variations.

HAZARD & PRECAUTIONARY STATEMENTS

H317: May cause an allergic skin reaction.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P321: Specific treatment (see label).
P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please refer to the product's Safety Data Sheet (SDS).

This technical data sheet is based on laboratory data obtained under standard conditions. For details not sufficiently covered above, please consult technical personnel. The manufacturer cannot be held responsible for any errors resulting from insufficient information. Our company reserves the right to amend this information. For detailed information regarding health, safety, transport risks, and precautions, refer to the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified under ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.