SAN DECO®
Paint Manufacturing & Distribution

BETON DECO EXTERIOR

Concrete Effect Decorative Coating

BETON DECO EXTERIOR is a decorative coating with lime additive that provides an exposed concrete appearance on the applied surface.

WATER BASED

LOW VOC

It allows the creation of various textures with different application techniques.

It has a high alkali ratio and does not cause blistering or cracking.

Although it prevents water penetration from the outside, it allows the moisture inside to escape, enabling the buildings to breathe.

It is water-based, environmentally friendly, and harmless to human health.

CONTENT: *Acrylic-based – water-based – lime-reinforced*	PACKAGING: *10 KG ; 20 KG*
THINNING: *Ready to use, do not dilute.*	DRYING TIME: *Drying Time Touch dry (at 23˚C): 5-6 hours* **drying time may be longer at higher relative humidity and lower temperature.*
PRIMER: *San Deco Decoprimer*	Fully Dry: *24-48 hours*
APPLICATION TOOL: *Trowel*	COLORING: -
NUMBER of COATS: *2*	VOC: *EU limit value (Directive 2004/42/EC) Category A/l: Decorative effect coatings (water-based): 200 g/l (2010) BETON DECO EXTERIOR contains a maximum of 47 g/l VOC.*
STORAGE and SHELF LIFE: *Can be stored unopened for 1 year in a cool, dry place between +5°C and +35°C, protected from frost and direct sunlight.*	

CONSUMPTION - Two Coats : *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.*

1 L covers 0.6–0.7 m^2,
1 kg covers 0.32–0.37 m^2.
Paint consumption per m^2: 1450–1650 ml and 2700–3100 g.

APPLICATION AREA

It can be applied to exterior mineral surfaces such as rough plaster, concrete, and cement board, as well as gypsum plaster, drywall, fixed plywood, and previously painted surfaces.

SURFACE PREPARATION

After cleaning all kinds of dirt, oil, flaking paints, and dust from the surface to be applied, surface defects should be repaired with San Deco Acrylic Putty Coarse and then primed with San Deco Decoprimer.

SURFACE CONDITIONS

During application and until the products are completely dry, attention should be paid to ensure that the ambient and surface temperature is at least +5°C and at most +35°C.

Application should not be carried out under direct sunlight.

The surfaces to be painted must be completely dry.

During application, ambient humidity should be below 75%.

The moisture content of the surface to be applied should be below 10%.

APPLICATION

Beton Deco Exterior should be mixed until it becomes homogeneous without thinning (if necessary, clean water may be added).

The first coat is applied to the surface with a trowel. After 5-6 hours, the second coat is also applied with a trowel. Various textures can be obtained with different application techniques.

For more detailed information about the application, product application videos can be viewed.

If more than one batch number is used in the same project, it is recommended to mix the batches in equal proportions before application to prevent batch differences.

Local retouching is not recommended. In retouching processes, it is recommended to reapply the entire damaged surface.

HAZARD & PRECAUTIONARY STATEMENTS AND EXPLANATIONS

H317: May cause allergic skin reactions.
P261: Avoid breathing dust/fume/gas/mist/vapor/spray.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P321: Specific treatment required (see label).
P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please refer to the product's Safety Data Sheet (SDS).

Since this technical data sheet is prepared based on laboratory data under normal conditions, please consult technical personnel for details that are not sufficient above. Otherwise, the manufacturer cannot be held responsible for errors that may occur as a result of insufficient information. The right to modify this information is reserved by our company. If necessary, detailed information about the health, safety, and transportation risks and precautions of the products can be found in the Material Safety Data Sheet.

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified to comply with ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.