SAN DECO®
Paint Manufacturing & Distribution

SANDECO ART EXTERIOR

Metallic Pearl Effect and Quartz Sand Decorative Coating

SANDECO ART EXTERIOR is a textured decorative coating developed for outdoor use, containing metallic pigments that create a gold and silver pearlescent finish with a granular appearance.



Has high UV resistance.

Provides excellent water vapor permeability, allowing moisture to escape and the surface to breathe.

Easy to apply, enabling the creation of various patterns and textures.

Water-based, environmentally friendly, and safe for human health.

CONTENT: *Acrylic-based – water-based*

THINNING: *Ready to use, do not dilute.*

PRIMER: *San Deco Decoprimer*

APPLICATION TOOL: *Sandeco Art: Brush*

NUMBER of COATS: *1*

STORAGE and SHELF LIFE:
Can be stored for 2 years between +5˚C and +35˚C, in its unopened packaging, in a cool and dry place protected from direct sunlight.

PACKAGING: *2,5 L ; 15 L*

DRYING TIME: *Drying Time Touch dry (at 23˚C): 4-5 hours*
**drying time may be longer at higher relative humidity and lower temperature.*

Fully Dry: *24 hours*

COLORING: *Sandeco Art Kartela*

VOC:
EU limit value (Directive 2004/42/EC)
Category A/l: Decorative effect coatings (water-based): 200 g/l (2010)
SANDECO ART EXTERIOR contains a maximum of 42.5 g/l VOC.

CONSUMPTION - Single Coat : *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.*

1 L covers 5–6.3 m^2,
1 kg covers 4–5 m^2.
Paint consumption per m^2: 160–200 ml and 200–250 gr.

APPLICATION AREA

Used on exterior surfaces such as walls, plaster, exposed concrete, and wood after proper surface preparation, with its compatible primer.

SURFACE PREPARATION

All dirt, oil, flaking paint, and dust must be removed from the surface before application.

Surface imperfections should be repaired with San Deco Acrylic Putty Coarse, followed by priming with San Deco Decoprimer.

SURFACE CONDITIONS

During application and until complete drying, the ambient and surface temperatures should be between +5°C and +35°C.

Avoid applying under direct sunlight.

Surfaces to be painted must be completely dry.

Ensure the ambient humidity is below 75%.

Ensure the surface moisture content is below 10%.

APPLICATION

Sandeco Art Exterior should be stirred homogeneously without thinning and applied to the surface with a brush in a single coat.

While still wet, patterns suitable to the desired appearance should be created using circular or linear brush movements.

Beyond the standard application technique, different decorative methods can be developed according to preference.

For more detailed application information, product application videos can be viewed.

If multiple batch numbers are used in the same project, mix them in equal proportions before application to prevent variations between batches.

Local retouching is not recommended. In case of damage, reapply the product to the entire affected area.

HAZARD & PRECAUTIONARY STATEMENTS AND EXPLANATIONS

H317: May cause an allergic skin reaction.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P321: Specific treatment (see label).
P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please refer to the product's Safety Data Sheet (SDS).

Since this technical data sheet is prepared based on laboratory data under normal conditions, please consult technical personnel for any details not specified above. Otherwise, the manufacturer cannot be held responsible for errors resulting from insufficient information. The right to revise this information is reserved by our company. For detailed information about health, safety, transport risks, and precautions, please refer to the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified to comply with ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.