

SAN DECO®
Paint Manufacturing & Distribution

TERAMIX HYDRO ULTRA

Exterior Coating with Water-Repellent Granular Texture

TERAMIX HYDRO ULTRA is a water-repellent, grain-textured, decorative exterior coating.

WATER BASED · LOW VOC · TINTABLE

Its water-repellent property prevents dirt accumulation.

The thick film layer formed during application conceals surface imperfections.

High resistance to UV rays, alkalis, and color fading.

Resistant to outdoor conditions such as rain, snow, humidity, and extreme temperatures.

Allows water vapor to escape through the surface, enabling the structure to breathe.

More elastic than cement-based products, bridging cracks on the substrate.

Water-based, environmentally friendly, and safe for human health.

CONTENT: *Acrylic-based – Water-based – Silicone-modified*	PACKAGING: *25 KG*
THINNING: *Ready to use; do not dilute.*	DRYING TIME: *Drying Time Touch dry (at 23˚C): 4-6 hours* **drying time may be longer at higher relative humidity and lower temperature.*
PRIMER: *San Deco Uniprimer*	Fully Dry: *24–48 hours*
APPLICATION TOOL: *Trowel*	COLORING: *Vision System*
NUMBER of COATS: *1*	VOC: *EU Limit Value (Directive 2004/42/EC) Category A/l: Decorative effect coatings (water-based): 200 g/L (2010) TERAMIX HYDRO ULTRA contains a maximum of 54.7 g/L VOC.*
STORAGE and SHELF LIFE: *Can be stored unopened for 2 years between +5°C and +35°C in a cool, dry place away from direct sunlight.*	

CONSUMPTION - Single Coat : *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.*

1 L covers 1.0–1.3 m^2
1 kg covers 0.65–0.75 m^2
Material consumption per 1 m^2: 950–1000 ml and 1400–1500 g.

APPLICATION AREA

Used as a coating material on exterior surfaces of all types of buildings, over rough plaster, fair-faced concrete, cement board, and thermal insulation systems, together with a suitable primer.

SURFACE PREPARATION

All dirt, oil, blistered paint, and dust should be cleaned from the surface before application.

Surface defects should be repaired with San Deco Acrylic Putty Thick, followed by priming with San Deco Uniprimer.

It is recommended to use a primer in the same color as the selected facade color.

SURFACE CONDITION

During application and until complete drying, ambient and surface temperature should be between +5°C and +35°C.

Do not apply under direct sunlight.

Surfaces must be completely dry before application.

Ambient humidity should be below 75%.

Surface moisture content should be below 10%.

APPLICATION

TERAMIX HYDRO ULTRA should be mixed thoroughly before application without dilution.

Apply one coat using a trowel. The application thickness should be adjusted according to the coarsest aggregate size in the product.

A plastic trowel can be used to create decorative circular textures on the surface.

If multiple production batches are used within the same project, mix them in equal proportions before application to avoid tonal or textural differences.

HAZARD & PRECAUTIONARY STATEMENTS

H317: May cause an allergic skin reaction.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364: Take off contaminated clothing and wash it before reuse.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P321: Specific treatment (see label).
P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more detailed information, refer to the product's Safety Data Sheet (SDS).

This technical data sheet is based on laboratory data obtained under standard conditions. For details not sufficiently covered above, please consult technical personnel. The manufacturer cannot be held responsible for any errors resulting from insufficient information. Our company reserves the right to amend this information. For detailed information regarding health, safety, transport risks, and precautions, refer to the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified under ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.